

GENUINE COMFORT

DELIVERING COMFORT CONSISTENTLY

Genuine Comfort Submittal Sheet

Job Name:		Engineer:	
Purchaser:		Architect:	
Unit No.:		Contractor:	
Schedule:		Submitted to:	
Location:		Submitted by:	
Comment:		Date Submitted:	

Model: GCTH01WD-C

Specifications:

Display range of temperature.....	32°F to 99°F (0°C to 40°C)
Control range of temperature	44°F to 90°F (7°C to 32°C)
Load rating.....	1 amp per terminal, 1.5 amp max all terminals combined
Display accuracy.....	+/- 1°F
Swing (cycle rate or differential)	Heating is adjustable from 0.2°F to 2.0°F Cooling is adjustable from 0.2°F to 2.0°F
Power Source	18 to 30 VAC, NEC Class II, 50/60 Hz for hardwire (common wire) Battery power from 2 AAA Alkaline batteries
Operating ambient.....	32°F to 105°F (0° to 41°C)
Operating humidity	90% non-condensing maximum
Dimensions of thermostat	4.72"W x 3.86"H x 1.1"D

GENUINE COMFORT

DELIVERING COMFORT CONSISTENTLY

Genuine Comfort Submittal Sheet

FEATURES

- Wired Thermostat
- Easy read display
- Blue back-light
- Easy access battery compartment
- Electric or Gas configurable
- Separate B & O terminals
- Separate heating and cooling swing (cycle rate) adjustments
- Room temperature calibration adjustment
- 3 minute compressor delay protection (selectable on or off)
- Easy wire color coded terminal blocks
- Mounts on wall
- Battery or 24v power
- 1 year limited warranty

