

GENUINE COMFORT

DELIVERING COMFORT CONSISTENTLY

Genuine Comfort Submittal Sheet

Job Name:		Engineer:	
Purchaser:		Architect:	
Unit No.:		Contractor:	
Schedule:		Submitted to:	
Location:		Submitted by:	
Comment:		Date Submitted:	

Model: GCTTW Electric Heat

Specifications:

GC THRU WALL AC			SPECIFICATIONS		
Model #			GCTTW-08ERA1	GCTTW-10ERA2	GCTTW-12ERA2
BTU			8,000	10,000	12,000
Control Type			Electronic	Electronic	Electronic
Certificate			UL	UL	UL
Power Supply		Ph-V-Hz	115V	230/208V	230/208V
Cooling	RATED Capacity	Btu/h	8,000	10,000	12,000
	RATED EER	Btu/w.h,w/w	2.81	2.81	2.78
	RATED CEER	Btu/w.h,w/w	9.6	9.6	9.5
	RATED Input	W	833	1042/1022	1263/1232
	RATED Current	A	7.8	4.6/5.0	5.5/7.5
Heating	RATED Capacity	Btu/h	4200	10600	10600/8600
	RATED Input(Heater)	W	1320	3450	3450/2821
	RATED Current	A	11.8	15.0	15/13.5
Starting Current		A	23.4	21	16.5
Indoor Air Circulation (Lo/Hi)		m3/h	344 / 459	430 / 498	409 / 487
Outdoor Air Circulation (Lo/Hi)		m3/h	440 / 635	680 / 820	595 / 715
Indoor Noise Level Db (Lo/Hi)		dB(A)	51.8 / 56.8	55 / 59.5	56 / 60
Outdoor Noise Level Db (Hi)		dB(A)	65.7	66	68
Operation Temp (Indoor)		°C - °C	17 - 32	17 - 32	17 - 32
Operation Temp (Outdoor)		°C - °C	18 - 43	18 - 43	18 - 43
Dimensions (WxDxH)		inch	24.21 x 20.28 x 14.53	24.21 x 20.28 x 14.53	24.21 x 20.28 x 14.53
Packing Dimensions (WxDxH)		inch	27.95 x 26.57 x 16.93	27.95 x 26.57 x 16.93	27.95 x 26.57 x 16.93
Net / Gross Weight		lbs	30 / 35	32 / 36	78 / 89
Plug Type		/	LCDI(5-15P)	LCDI(6-20P)	LCDI(6-20P)
Refrigerant Type		/	R410A	R410A	R410A
Design Pressure		psi	300 / 520	300 / 520	300 / 520
Loading Capacity (40HQ)		SET	306	306	306

GENUINE COMFORT

DELIVERING COMFORT CONSISTENTLY

Genuine Comfort Submittal Sheet

FEATURES

- Universal Thru-Wall Size
- Fits Universal Sized TTW Sleeves
- Digital Controls
- Remote Control Included
- UL Certified
- Slide-Out Washable & Easy-Clean Filter
- 24-Hour Programmable Timer
- Dehumidify Mode
- Trim Piece Included
- **Genuine Care Warranty:**
1 Year Unit Replacement

