

GENUINE COMFORT

DELIVERING COMFORT CONSISTENTLY

Wireless Wall Thermostat | Spec Sheet | Model GCTH01WS-C

Features

- Wireless Thermostat
- Easy Read Display
- Blue Back-Light
- Easy Access Battery Compartment
- Electric or Gas Configurable
- Separate B & O Terminals
- Separate Heating and Cooling Swing (Cycle Rate) Adjustments
- Room Temperature Calibration Adjustments
- 3 Minute Compressor Delay Protection (Selectable On or Off)
- Easy Wire Colour Coded Terminal Blocks
- Mounts on Wall or Junction Box
- Battery or 24V Power
- 1 Year Limited Warranty

Product Photo



Wireless Wall Thermostat

1 Stage Heat, 1 Stage Cool Conventional
2 Stage Heat, 1 Stage Cool Heat Pump
Non-Programmable

Specifications

Display Range of Temperature.....	32°F to 99°F (0°C to 40°C)
Control Range of Temperature.....	44°F to 90°F (7°C to 32°C)
Load Rating.....	1 amp per terminal, 1.5 amp max all terminals combined
Display Accuracy.....	+/-1°F
Swing (Cycle Rate or Differential).....	Heating and Cooling are adjustable from 0.2°F to 2°F
Power Source.....	18 to 30 VAC, NEC Class II, 50/60Hz for hardwire (common wire) Battery power from 2 AAA Alkaline batteries
Operating Ambient.....	32°F to 105°F (0°C to 41°C)
Operating Humidity.....	90% non-condensing maximum
Dimensions of Thermostat.....	4.72"W x 3.86"H x 1.1"D
Frequency.....	433.92MHz

For More Information, Please Contact: (204) 201-0717 // 1-(866) 233-4022
info@genuinecomfort.com or visit www.genuinecomfort.com