

DELIVERING COMFORT CONSISTENTLY

Genuine Comfort Submittal Sheet

Job Name:	Engineer:	
Purchaser:	Architect:	
Unit No.:	Contractor:	
Schedule:	Submitted to:	
Location:	Submitted by:	
Comment:	Date Submitted:	

Model: GCPAC

Specifications:

вти		10,000	12,000	14,000	
Model #		GCPAC-10CPA	GCPAC-12CPA	GCPAC-14CPA	
Control Type		Electronic	Electronic	Electronic	
Remote Control		Yes	Yes	Yes	
Certificate			UL/DOE	UL / DOE	UL/DOE
Voltage & Frequency		Ph-V-Hz	115V / 60Hz	115V / 60Hz	115V / 60Hz
	Cooling Capacity	BTU/Hr	10,000	12,000	14,000
Cooling	Cooling Power Input	W	1045	1330	1365
	Cooling Current Input	А	9.1	12	11.7
	EER	BTU/Wh	9.55	9	9.89
Indoor Air Circulation (Lo/Hi)		m3/h	251/301	345 / 419	445 / 540
Indoor Noise Level Db (Lo/Hi)		dB(A)	51.5 / 55.0	52.5 / 54.5	53 / 57.5
Outdoor Noise Level Db		dB(A)	59.0	58.5	60
Operation Temp		°C - °C	17 - 35	17 - 35	17 - 35
Dimensions (WxDxH)		inch	13.98 x 13.58 x 27.68	17.87 x 14.37 x 27.56	18.39 x 15.63 x 30.12
Packing Dimensions (WxDxH)		inch	15.75 x 14.96 x 34.25	19.29 x 15.94 x 34.25	20.16 x 17.40 x 34.65
Net / Gross Weight		lbs	53 / 62	62 / 73	77 / 88
Plug Type			LCDI(5-15P)	LCDI(5-15P)	LCDI(5-15P)
Refrigerant Type		Name	R32	R32	R32
Loading Capacity (40HQ)		SET	534	405	353

GENUINE COMFORT


DELIVERING COMFORT CONSISTENTLY

Genuine Comfort Submittal Sheet


FEATURES

- Digital Controls
- Remote Control Included
- UL / DOE Certified
- Single Hose Setup
- Dehumididy Mode
- Energy Saver Mode
- Genuine Care Warranty
 - 1 Year Full Replacement Warranty









Unit Dimension	W(mm)	H(mm)	D(mm)
small body	454	700	365
big body	467	765	397